

# Configuration of Parallel Real-Time Applications on Multi-Core Processors

Mohammad Samadi Gharajeh

Tiago Carvalho

Luis Miguel Pinho

School of Engineering, Polytechnic Institute of Porto, Portugal

July 2022

# Agenda

- Introduction
- The Suggested Approach
- Measurement Process
- Heat Benchmark
- Hardware Platform
- Evaluation

# Introduction

- **Goal:** Using parallel programming models to improve the performance of real-time applications in modern processors
- **Constraints:** Applying static timing analysis for simpler models or measurement-based analysis using traditional platforms (or considering only sequential algorithms)
- **Motivation:** Providing an efficient configuration for the allocation of the parallel program in the computing units of the processor

# The Suggested Approach


We have suggested a measurement-based approach to

- Assess the execution time of OpenMP tasks
- Analyze the importance of doing a timing analysis
- Specify proper configurations of OpenMP directives
- Identify critical tasks
- Understand the predictability of the system/application

# The Suggested Approach

## Goals:


- Studying the behavior of the application using measurement results
- Selecting the best configuration for the allocation of the parallel program
- Identifying critical tasks for reducing the need to measure at runtime
- Reducing the runtime overhead



# Measurement Process

Measuring the program with Linux perf under different numbers of threads

- $N$ : the number of tasks
- $M$ : the number of threads
- $t\_id$ : the identifier of the current task
- $thr\_id$ : the thread number



# Measurement Process

```
#pragma omp task
{
    /* Start the measurement process for t_id */
    /* Get the monitor of the current thread */
    uint32_t thread_num = omp_get_thread_num();
    xavier_monitor_t monitor = monitors[thread_num];

    if ((task_no == -1) || (task_no == t_id)) {
        /* Start measuring the events */
        xavier_reset(&monitor);
        xavier_enable(&monitor);
    }

    code();

    /* Terminate the measurement process for t_id */
    if ((task_no == -1) || (task_no == t_id)) {
        /* Stop measuring the events */
        xavier_disable(&monitor);


        /* Get measurement results of the events */
        xavier_result_t results;
        xavier_read(&monitor, &results);

        Store measurement results();
    }
}
```

# Heat Benchmark


## Characteristics:

- Applying an iterative Gauss-Seidel method to solve the heat equation
- Explaining the distribution of heat in a given region over time
- Including 64 tasks
- Containing a sophisticated TDG




# Hardware Platform

The OpenMP-based heat benchmark has been evaluated on a Jetson AGX Xavier, in terms of the number of CPU cycles and cache-level metrics.




CPU COMPLEX




VOLTA GPU

# Evaluation






4 active cores



8 active cores

# Evaluation






## Coefficient of Variance

(a) 4 active cores, 2 OMP threads

(b) 4 active cores, 4 OMP threads

(c) 4 active cores, 8 OMP threads

# Evaluation



## Coefficient of Variance

(a) 8 active cores, 2 OMP threads


(b) 8 active cores, 4 OMP threads

(c) 8 active cores, 8 OMP threads

# Evaluation



L2 miss ratio mean (min = 0.22, max = 0.43)



Coefficient of Variance for L2 miss ratio (min = 0.03, max = 0.20)

# THANKS



**For more information:**  
[mmasa@isep.ipp.pt](mailto:mmasa@isep.ipp.pt)